



4. Comfortable and spacious driver's area

Easy to move around and work, reducing fatigue and enabling all-day productivity.

5. 4-Direction adjustable seat

A spacious, soft and comfortable seat with 4 adjustable directions up, down, forward and backward to accommodate the operator's body.

*Model B2740s only

6. Left/right fender handles

Helps the operator get on and off the tractor safely and conveniently while providing stability for the operator when working in rough terrain.



Precise area measurement and task management

Able to calculate area in rai/ngan, track income and expenses, and organize work schedules. Manages your work professionally.



Accurate update on every movement

Indicates the coordinate and operating area of an individual or a group of machine. Real-time* monitoring of engine status** is also available.

Note: *Performance may vary depending on the machine speed or internet speed./ **Indicates operating status such as engine stop, engine start, key switch Off, 5-minute idling, and machine traveling.



Anti-theft alarm

Operating perimeters for the machine can be set. An alert will be issued if the machine goes out of these perimeters.

Note: This function is operable if the engine is turned off for no later than 1 month, or if there is an attempt to disconnect the signal receiver box from the machine.



Efficient maintenance

Notifies maintenance at appropriate intervals and indicates battery status.

KUBOTA Tractor *B-SERIES* Specifications

Tractor			B2140SN-B	B2140S-B	B2440S-B	B2740S-B
Engine						
Type			E-TVCS, liquid cooled, 3-cylinder diesel			
Model			D1005-E4-D35T	D1005-E4-D35	D1105-E4-D35	D1305-E4-D35
Engine gross power*		kW (PS)	21.3		24.3	27.3
PTO power*		kW (PS)	17.3		19.4	21.2
Bore and stroke		mm	76 x 73.6		78 x 78.4	78 x 88.0
Total displacement		cc	1,001		1,123	1,261
Rated revolution		rpm	2,600			
Maximum torque		N·m	58.3		70	80.9
Battery			55B24L-MF			
Fuel tank Capacity		L	23			
Fuel type			Diesel fuel (B7, B10 and B20)			
Travel system			Four-wheel drive (4WD)			
Tire size	Front	in.	5-12		180 / 85D12	
	Rear	in.	8-18		8.3-20	
Steering			Standard steering		Power steering	
Transmission			Gear shift 9 forward, 3 Reverse			
Brake Systems			Wet disk type			
Clutch			Dry single plate			
Min. turning radius (with brake)		m	2.1			
PTO						
Rear-PTO			SAE 1-3/8, 6 splines			
PTO (Engine speed)		rpm	540 (2,504) / 980 (2,510)			540 (2,535) / 750 (2,542)
Hydraulic system						
Pump capacity		L / min	16.6			26.4
Hydraulic control system			Position control			Position control, Draft control and Mix control
3-Point hitch			ISO Category 1N			
Max. lifting force	At lifting point	kg	750			
	24 in. behide lift point	kg	590			
Dimension						
Weight		kg	615	635	650	660
Overall length without 3P		mm	2,387		2,407	
Overall width		mm	1,000 / 910		1,105 / 1,015	
Overall height (with ROPS)		mm	1,940		1,960	
Min. ground clearance		mm	300		325	
Tread	Front	mm	705	780	815	
	Rear	mm	700 / 790	810 / 900		

Note: The company reserves the right to change any details without prior notice.
Operating instructions: To obtain optimal operation, read the operating instructions from the Operation and Maintenance Manual of each KUBOTA tractor. For more information, please consult the local KUBOTA tractor dealers nationwide.

SIAM KUBOTA Corporation Co., Ltd.

101/19-24, Moo 20, Navanakom Industrial Estate,
Tambon Khlongnuang Amphur Khlongnuang, Pathumthani 12120
Tel: +66 (0) 2909 0300 Fax: +66 (0) 2909 1698
Published in March 2025
www.siamkubota.co.th | Siam Kubota



KUBOTA Tractor

B-SERIES 21 - 27 HP




Everything
You Need
for Any Sugarcane Tasks



ALL YOU NEED...for sugarcane furrow maintenance

A single machine to meet all your needs year-round



ALL YOU NEED...for mobility in sugarcane furrow

Optimal performance designed exclusively for sugarcane farmers



Automatic implement control system* (Draft Control)

The automatic implement leveler system keeps implements at the desired height, even when they dig too deep into the soil or encounter hard ground. This provides optimal performance, mobility and reduced seizing, while improving operator comfort and contributing to fuel savings.**

*Model B2740S only **From operation test in sugarcane farm, Kanchanaburi. The comparison was made between Draft Control ON/OFF to measure fuel consumption rate and tested with a fertilizer ripper.



Resilience and power to take on tough jobs

The 4-Wheel Drive (4WD) system maximizes power and traction to handle tough tasks. Power is evenly distributed to all four wheels, minimizing the risk of wheel slip during operation. All of this is further supported by a robust hydraulic system.

Body dimensions specifically tailored for operation between sugarcane rows

With a front width of only 91 cm for the B2140SN and 101.5 cm for the B2140S, B2440S and B2740S models, maintenance in sugarcane furrow is made even more efficient and convenient with KUBOTA Tractor B-Series.



101.5 cm

Wide range of shifting levels for quality work

A versatile 9 forward and 3 reverse shifting system lets you adjust the tractor speed to match your needs and implements, ensuring the work quality you desire.



Maximum mobility with Power Steering

Effortless steering with minimal force allows for greater control even in tight spaces. With a turning radius of just 2.1 m, headland turns are made simpler and more fluid.




Turning radius 2.1 m



ECO-PTO : Delivers excellent quality and fuel saving*

2 selectable PTO levels at 540 and 750 rpm are just what the farmers need to produce quality specialized work ranging from rotary tilling to produce highly fine soil or general-purpose fine mist sprayer.

With PTO speed at 540 / 750 rpm (B2740S only)



Engine

The KUBOTA B-SERIES Tractor, 21-27 HP, features a brand new indirect-injection, 4-stroke, 3-cylinder KUBOTA Diesel Engine equipped with a water-cooling system that delivers high torque performance.



Great value with B20 compatibility


Save up to 3.25 Baht/liter* on refueling cost while being environmentally friendly reducing PM2.5 fine particles and supporting local palm plantations.

*Comparison between the B20 diesel and B7 diesel as of September 1, 2020.

ALL YOU NEED ...for safety and comfort, meeting KUBOTA standards

Comprehensive implements to handle any task implements to handle any tasks in the sugarcane furrow

Complete any tasks with **TRA CHANG** standard implements designed exclusively for KUBOTA Tractor



1. ROPS and safety belt from Japan

Enhance safety level with ROPS (Rollover Protective Structures) and safety belt to protect the operator in case of tractor rollover.

2. Multi-reflective headlight

Travel safely at night with a multi-reflective headlight that provides a wide illumination range and superior brightness compared to standard headlights, ensuring a clearer view and safer operation.

3. Yoke draw bar assembly

Designed for immediate attachment to agricultural trailers without the need for any modifications.

TRA CHANG Sugarcane Guard SG270/SG270S

Designed for KUBOTA Tractor B2140S / B2140SN / B2440S and B2740S models, this robust and durable implement ensures operator safety while minimizing contact with sugarcane leaves in the interrow. Its black color enhances visibility.



TRA CHANG Rotary RX80A / RX85B / RX135B

With a front width of 85 cm, this implement is an ideal choice for sugarcane furrow. The blades, imported from Spain, are durable through hardening process, with perfect design for fine soil tilling while remaining lightweight and fuel-efficient.

Details	RX80A	RX85B	RX135B
Traveling system	Bevel gears 1.46:1		
Chain case	Transmit power through the side roller chains		
Dimension	900 x 700 x 960 mm	980 x 700 x 960 mm	1,530 x 810 x 950 mm
Weight	150 kg	155 kg	187 kg
Operating width	720 mm	800 mm	1,325 mm
Blade type	C		
Number of blades	8 pcs	12 pcs	21 pcs
Revolution speed (blade shaft/PTO shaft)	221/540 rpm	184/540 rpm	184/540 rpm
Suitable applications	Tilling and weeding in sugarcane furrow		
Compatible tractors	B2140SN / B2140SN-B	B2140S / B2140S-B / B2440S / B2440S-B / B2740S / B2740S-B	B2140S / B2140S-B / B2140SN / B2140SN-B / B2440S / B2440S-B

TRA CHANG Disc Harrow DH205A / DH205B

Robust discs comes equipped with Japan-imported bearings to ensure quality. The furrow is adjustable just right for your applications, delivering fine, clean plowing.

Details	DH205A	DH205B
Disc size	20 in.	
No. of discs	5 pcs	
Width x length x height	1,230 x 1,705 x 890 mm	1,230 x 1,705 x 860 mm
Weight	185 kg	201 kg
Compatible soil	All soil type	
Compatible tractors	B2140S / B2140S-B / B2140SN / B2140SN-B	B2440S / B2440S-B / B2740S / B2740S-B



TRA CHANG Disc Plow DP184A / DP203B

With three adjusting holes, the working height can be set to three different positions to accommodate a variety of soil conditions, from regular to extremely hard.

Details	DP184A	DP203B
Disc size	18 in.	20 in.
No. of discs	4 pcs	3 pcs
Width x length x height	1,030 x 1,560 x 970 mm	960 x 1,880 x 910 mm
Weight	160 kg	210 kg
Compatible soil	All soil type	
Compatible tractors	B2140S / B2140S-B / B2140SN / B2140SN-B	B2440S / B2440S-B / B2740S / B2740S-B



KUBOTA Special Dozer SD132

The integrated, durable dozer blade is designed without seams to prevent breakage at the joints. Additionally, the dozer frame is positioned higher to enhance mobility during operation and the control panel is conveniently located near the driver's hand for easy access.

Details	SD132
Compatible tractors	B2140S B2440S/B2740S
Blade dimensions (width x length)	1,330 x 410
Height from ground to dozer (at highest raised level)	375-410
Ground clearance (from ground to dozer frame)	285
Time to detach the dozer assembly from a tractor	5-6"
Time to attach the dozer assembly to a tractor	8-9"
Dozer position control system	Double-acting hydraulic system
Hydraulic cylinder (inner diameter x stroke)	25 x 380
Weight	238
Compatible tractors	B2140S / B2140S-B / B2440S / B2440S-B / B2740S / B2740S-B



*Varies based on each operator's skill.

ALL YOU NEED ...A complete service, meeting KUBOTA standards



2-years or 1,500-hours warranty
Whichever comes first with periodic inspection of tractors is provided to ensure reliability
It is recommended to read the warranty conditions and contents from the warranty book and warranty card.



KUBOTA Genuine Spare Parts
A selection of over 80,000 spare parts is available at SIAM KUBOTA authorized dealers and online KUBOTA Store.



SIAM KUBOTA Service Hotline 1747
Give advice on operation, maintenance, technical problems, and service appointment. Available daily from 7.00 - 19.00 without any days off.



KM Maintenance Package of 1 year or 200 hours (whichever comes first)
- Free inspection service of 3 times / 1 year
- Free spare part maintenance of 1 year or 200 hrs.



Khum Aun Jai Program
Provides 2 free inspection services at the 2nd year mark.
(Free service fees and technician travel expenses, 20% off maintenance spare parts.)



KUBOTA Service Care
Offers inspection service for tractors that are out of warranty coverage, including free checkup and discounts on spare parts as specified by SIAM KUBOTA.



KUBOTA Agricultural Machinery Driving School
Learn tractor driving skills for safe and proper operation.



SIAM KUBOTA Service Center
Comprehensive after-sales services are provided with standardized nationwide service centers and authorized dealers.



SIAM KUBOTA VIP Program
Get 20% off spare parts or gifts on special occasions.



KUBOTA FAMILY
Earn points by purchasing KUBOTA products and spare parts, then redeem them for discounts on spare parts or choose from a variety of gifts.



SIAM KUBOTA Leasing
Down payment of KUBOTA and TRA CHANG products is possible via SIAM KUBOTA Leasing Co., Ltd.